

SPECIFICATIONS		CABLE GROUPS	
<b>ELECTRICAL SPECIFICATIONS</b> IMPEDANCE: 75 Ω WORKING VOLTAGE RATING: 500 VRMS FREQUENCY RANGE: 0-1 GHz  <b>MECHANICAL SPECIFICATIONS</b> MATING: 3/8 - 32 THREAD CABLING: CRIMP  <b>PLATING</b> G - GOLD N - NICKEL T - TIN  <b>DIELECTRIC MATERIAL</b> PE - POLYETHYLENE PP - POLYPROPYLENE	<b>GRP</b>	<b>FOR THESE CABLE TYPES</b>	
	D	RG-59, 59A, 59B, 62, 62A, 62C/U; ALPHA 9059, 9062, 9830, 9840, 9845; BELDEN 7807A, 8221, 8241, 9169, 9204, 9228; CANARE LV-61S; COMMSCOPE 5555, 5560, 5563; HARBOUR HPF200	
	Q	RG-6/U TYPE; BELDEN 1694A, 9248; COMMSCOPE 5715, 5729, 5765	
	Q3	ALPHA 9006A; BELDEN 8215; BICCGENERAL C5810; CAROL/COLUMBIA C5810; COLEMAN 8418, 988418, M17/2-RG6; COMMSCOPE 5710; CONSOLIDATED 4433; CZ Labs 3403P; Dearborn D4204; Huber+Suhner G 05133 D, RG 6 A/U; International Electronic Wire & Cable Company 4002; Manhattan M4204; Times Microwave 17-05-92 QPL, 17-663-83, AA-3810, AA-7276, LSSB-RG6, M17/180-00001, M18/2-RG6; Weico Wire W006A	
<b>FOR A MORE EXTENSIVE LISTING OF CABLE GROUPS, PLEASE REFER TO PAGES 134-145</b>			

COMPRESSION CONNECTOR  
See compression tools on previous page.



FIG. 1  
RFF-1401-D, -Q, -Q3



FIG. 2  
RFF-1402-08



FIG. 3  
RFF-1402-D



FIG. 4  
RFF-1442, -03, -1



FIG. 5  
RFF-1444



FIG. 6  
RFF-1445-5, -5-1



FIG. 7  
RFF-1446-10



FIG. 8  
RFF-1448



FIG. 9  
RFF-1450-03



FIG. 10  
RFF-1476, -1



FIG. 11  
RFF-1477

PHOTOS FOR REFERENCE ONLY, SHOWN AT 100% ACTUAL SIZE.

FOR MOUNTING CONFIGURATIONS REFER TO PAGES 149-164

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOMMENDED TOOL
					BDY	P/C	DIE	
RFF-1401-D	1	MALE COMPRESSION CRIMP PLUG		BLACK BAND, FOR RG-59/U	N	T	PE	RFA-4004-20
RFF-1401-Q	1	MALE COMPRESSION CRIMP PLUG	Q	RED BAND, FOR RG-6/U	N	T	PE	RFA-4004-20
RFF-1401-Q3	1	MALE COMPRESSION CRIMP PLUG	Q3	BLUE BAND, FOR RG-6/U QUAD	N	T	PE	RFA-4004-20
RFF-1402-08	2	MALE CRIMP	Q	NO PIN, WITH GASKET & SILICON, FOR RG-6/U	--	--	PE	RFA-4005-306
RFF-1402-D	3	MALE CRIMP	D	FOR RG-59/U	N	N	PE	RFA-4005-306
RFF-1442	4	FEMALE RIGHT ANGLE PCB MOUNT		4 LEG, LONG	N	T	PE	
RFF-1442-03	4	FEMALE RIGHT ANGLE PCB MOUNT		4 LEG, LONG	N	T	PP	
RFF-1442-1	4	FEMALE RIGHT ANGLE PCB MOUNT		4 LEG, SHORT	N	T	PP	
RFF-1444	5	FEMALE BULKHEAD		WITH HEX FLANGE & SOLDER TAB	N	T	PP	
RFF-1445-5	6	ADAPTER		F MALE QUICK DISCONNECT TO F FEMALE	N	T	PE	
RFF-1445-5-1	6	ADAPTER		F MALE QUICK DISCONNECT TO F FEMALE	G	G	PE	
RFF-1446-10	7	RIGHT ANGLE ADAPTER		F MALE TO F FEMALE	N	N	PE	
RFF-1448	8	ADAPTER		F MALE TO F MALE	N	N	PE	
RFF-1450-03	9	FEMALE VERTICAL PCB MOUNT		4 LEG, .32" ON CENTER, TAB CONTACT	N	T	PE	
RFF-1476	10	ADAPTER		F FEMALE TO F FEMALE	N	T	PE	
RFF-1476-1	10	ADAPTER		F FEMALE TO F FEMALE	G	T	PE	
RFF-1477	11	BULKHEAD ADAPTER		F FEMALE TO F FEMALE	N	T	PE	