



MALE		FEMALE																																															
	<table border="1"> <thead> <tr> <th rowspan="2">LETTER</th> <th colspan="2">INCHES [MILLIMETERS]</th> </tr> <tr> <th>MINIMUM</th> <th>MAXIMUM</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>.019 [0.48]</td> <td>.021 [0.52]</td> </tr> <tr> <td>B</td> <td>-</td> <td>.045 [1.14]</td> </tr> <tr> <td>C</td> <td>-</td> <td>.217 [5.51]</td> </tr> <tr> <td>D</td> <td>.213 [5.41]</td> <td>.224 [5.69]</td> </tr> <tr> <td>E</td> <td>.039 [0.99]</td> <td>.040 [1.02]</td> </tr> </tbody> </table>	LETTER	INCHES [MILLIMETERS]		MINIMUM	MAXIMUM	A	.019 [0.48]	.021 [0.52]	B	-	.045 [1.14]	C	-	.217 [5.51]	D	.213 [5.41]	.224 [5.69]	E	.039 [0.99]	.040 [1.02]		<table border="1"> <thead> <tr> <th rowspan="2">LETTER</th> <th colspan="2">INCHES [MILLIMETERS]</th> </tr> <tr> <th>MINIMUM</th> <th>MAXIMUM</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>.118 [3.00]</td> <td>.120 [3.05]</td> </tr> <tr> <td>B</td> <td>.159 [4.04]</td> <td>.163 [4.14]</td> </tr> <tr> <td>C</td> <td>.020 [0.51]</td> <td>.024 [0.61]</td> </tr> <tr> <td>D</td> <td>.045 [1.14]</td> <td>-</td> </tr> <tr> <td>E</td> <td>.228 [5.79]</td> <td>.232 [5.89]</td> </tr> <tr> <td>F</td> <td>.252 [6.40]</td> <td>.256 [6.50]</td> </tr> <tr> <td>G</td> <td>.039 [0.99]</td> <td>.040 [1.02]</td> </tr> </tbody> </table>	LETTER	INCHES [MILLIMETERS]		MINIMUM	MAXIMUM	A	.118 [3.00]	.120 [3.05]	B	.159 [4.04]	.163 [4.14]	C	.020 [0.51]	.024 [0.61]	D	.045 [1.14]	-	E	.228 [5.79]	.232 [5.89]	F	.252 [6.40]	.256 [6.50]	G	.039 [0.99]	.040 [1.02]
LETTER	INCHES [MILLIMETERS]																																																
	MINIMUM	MAXIMUM																																															
A	.019 [0.48]	.021 [0.52]																																															
B	-	.045 [1.14]																																															
C	-	.217 [5.51]																																															
D	.213 [5.41]	.224 [5.69]																																															
E	.039 [0.99]	.040 [1.02]																																															
LETTER	INCHES [MILLIMETERS]																																																
	MINIMUM	MAXIMUM																																															
A	.118 [3.00]	.120 [3.05]																																															
B	.159 [4.04]	.163 [4.14]																																															
C	.020 [0.51]	.024 [0.61]																																															
D	.045 [1.14]	-																																															
E	.228 [5.79]	.232 [5.89]																																															
F	.252 [6.40]	.256 [6.50]																																															
G	.039 [0.99]	.040 [1.02]																																															
SPECIFICATIONS		CABLE GROUPS																																															
<b>ELECTRICAL SPECIFICATIONS</b> IMPEDANCE: 50 Ω WORKING VOLTAGE RATING: 250 VRMS @ SEA LEVEL FREQUENCY RANGE: 0-4 GHz  <b>MECHANICAL SPECIFICATIONS</b> CABLING: CRIMP AND PCB SOLDER INTERFACE: CECC 22230  <b>PLATING</b> N - NICKEL G - GOLD  <b>DIELECTRIC MATERIAL</b> T - TEFLON		<b>GRP</b> <b>FOR THESE CABLE TYPES</b>																																															
		B	TIMES LMR-100A; RG-174, 188, 188A, 316/U; ALPHA 9174, 9316; BELDEN 7805A, 8216, 83269, 83284, 84316; COMMSCOPE AMC-174																																														
		B1	RG-316/U DOUBLE SHIELD; RD-316																																														
FOR A MORE EXTENSIVE LISTING OF CABLE GROUPS, PLEASE REFER TO PAGES 134-145																																																	



PHOTOS FOR REFERENCE ONLY, SHOWN AT 150% ACTUAL SIZE.

FOR MOUNTING CONFIGURATIONS REFER TO PAGES 149-164

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOMMENDED TOOL
					BDY	P/C	DIE	
RF123-7000-B	1	MALE SNAP ON CRIMP	B	FOR RG-174/U	N	G	T	RFA-4009-204
RF123-7000-B-03	2	MALE PUSH ON CRIMP	B,B1	FOR RG-174/U, RG-316/U & RG-316/U DOUBLE SHIELD	N	G	T	RFA-4009-204
RF123-7000-B1	2	MALE SNAP ON CRIMP	B1	FOR RG-174/U & RG-316/U DOUBLE-SHIELD	N	G	T	RFA-4009-204
RF123-7001-B	3	MALE SLIDE ON CRIMP	B	FOR RG-174/U	N	G	T	RFA-4009-204
RF123-7002-B	4	MALE SCREW ON CRIMP	B	FOR RG-174/U	N	G	T	RFA-4005-300
RF123-7050-1B	5	FEMALE SLIDE ON CRIMP	B	FOR RG-174/U	G	G	T	RFA-4009-204
RF123-7050-1B1	5	FEMALE SLIDE ON CRIMP	B,B1	FOR RG-174/U, RG-316/U & RG-316/U DOUBLE SHIELD	G	G	T	RFA-4009-204
RF123-7052-1B	6	FEMALE CRIMP BULKHEAD	B	WITH DOUBLE D FLAT, FOR RG-174/U	G	G	T	RFA-4009-204
RF123-7300-1	7	FEMALE RIGHT ANGLE PCB BULKHEAD		WITH DOUBLE D FLAT, 4 LEG	G	G	T	
RF123-7350-1	8	FEMALE VERTICAL PCB BULKHEAD		4 LEG	G	G	T	