

## 7-16 DIN ADAPTERS

## PLATING SPECIFICATIONS

**BODY:** S - SILVER    **PIN/CONTACT:** S - SILVER    **DIELECTRIC:** T - TEFLON  
**INTERFACE**    **IMPEDANCE:** 50 Ω    **FREQUENCY RANGE:** 0 TO 7.5 GHZ    **PIM:** ≥ -.150 DBC



FIG. 1  
RFD-1650-2



FIG. 2  
RFD-1652-2



FIG. 3  
RFD-1653-2



FIG. 4  
RFD-1658-2



FIG. 5  
RFD-1660-2



FIG. 6  
RFD-1670-2



FIG. 7  
RFD-1671-2



FIG. 8  
RFD-1672-2



FIG. 9  
RFD-1673-2

PHOTOS FOR REFERENCE ONLY, SHOWN AT 75% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	NOTES	PLATING		
				BDY	P/C	DIE
RFD-1650-2	1	BARREL ADAPTER	7-16 DIN MALE TO 7-16 DIN MALE	S	S	T
RFD-1652-2	2	RIGHT ANGLE ADAPTER	7-16 DIN MALE TO 7-16 DIN FEMALE	S	S	T
RFD-1653-2	3	BARREL ADAPTER	7-16 DIN FEMALE TO 7-16 DIN FEMALE	S	S	T
RFD-1658-2	4	RIGHT ANGLE ADAPTER	7-16 DIN FEMALE TO 7-16 DIN FEMALE	S	S	T
RFD-1660-2	5	BARREL ADAPTER	7-16 DIN FEMALE TO 7-16 DIN MALE	S	S	T
RFD-1670-2	6	ADAPTER	7-16 DIN MALE TO N MALE	S	S	T
RFD-1671-2	7	ADAPTER	7-16 DIN MALE TO N FEMALE	S	S	T
RFD-1672-2	8	ADAPTER	7-16 DIN FEMALE TO N MALE	S	S	T
RFD-1673-2	9	ADAPTER	7-16 DIN FEMALE TO N FEMALE	S	S	T